

Restrooms • Lounges • Bowling Alleys • Conference Rooms i Schools
Smoking Rooms i Restaurants i Loading Docks i Fire Stations



AQC-12 120 VAC

AQC-21 12-24 VAC or VDC


- Detects cigarette smoke, VOCs and many other gases.
- UPON ALARM
 - AQC closes SPDT relay to a control panel or other device.
- Easy installation, unit mounts flush in a standard 4 x 4 electrical box.
- No maintenance required, sensors have a 7 to 10 year life expectancy.
- Detectors have customer adjustable settings for:
 - a) sensitivity of the unit to smoke and gases.
 - b) Time of activation of relay closure.
- LED lights show the status of the detector.
- The AQC-12 and AQC-21 both have supervised sensors and will go into alarm condition if there is an internal failure of the unit.
- Automatic operation; units automatically reset after alarm or power outage.
- General purpose detector for cigarette smoke, diesel fumes, VOCs and other hydrocarbons. Primary use is detection of cigarette smoke in non-smoking areas.

Note: These units are not suitable as smoke alarms, fire alarms or carbon monoxide detectors. For detection of a specific gas please consult Macurco for the proper detector.


Recommended Coverage: 900 sq. feet.
All units are 100% Gas Tested
i Solid-State Sensor: Maintenance Free

TYPICAL WIRING DIAGRAMS

The AQC-12 provides Automatic Fan Control



The AQC-12 will typically be connected to a standard Class A or B alarm control panel, providing a relay closure upon alarm. This system uses the alarm control panel to identify the location of the alarm.



Specifications

Power: Size: Mounting Box: Relay: Sensitivity: Time Adjustment: Maintenance: Color: Shipping Weight: **AQC-12**

120 VAC 4.5 x 4.5 x 1.75 inches standard 4 x 4 elec. box 5 amp SPDT @ 120VAC adjustible 1 to 10 minutes none required white one pound

AQC-21

12-24 VAC or VDC 4.5 x 4.5 x 1.75 inches standard 4 x 4 elec. box 5 amp SPDT @ 120VAC adjustible 1 to 10 minutes none required white one pound