

# Zeta II



Zeta II continues to be popular for many types of installations. The shallow, unobtrusive profile neatly blends into any environment and is further enhanced by the semi-recessing trim plate. Competitively priced, Zeta II has full BSI Kitemark and ICEL approvals as well as an IP65 weatherproof rating. The range also includes central addressable self-test and slave variants, all with an easy to install first fix base and removable geartray.

Whether it is being utilised in offices, pubs, corridors or exterior locations, Zeta II delivers dependable safety at a value for money price level.

- BSI kitemarked for peace of mind
- ICEL registered with verified light performance
- Competitive IP65 weatherproof range
- Simple first fix base with removable geartray
- Exit legend kit available
- Available in self-contained, AC/DC and AC mains slave versions
- EasiCheck and CeaGuard Self-test options
- Supplied with lamp

### Lamp Options

- 8W T5 fluorescent, 3500°K - G5 cap

### Materials

- Base - Flame retardant ABS, white finish
- Diffuser - Linear reeded clear polycarbonate
- Recessing Trim Plate - Steel, powder coated in RAL9016 white finish
- Batteries (self-contained versions) - NiCd

### Installation Notes

- Suitable for ceiling or wall mounting
- BESA entry drill-outs on rear. Cable entries on ends
- Geartray and diffuser clip into position. Removal requires tool to release clips
- Supplied complete with 1 x 8W lamp

### Options


- Maintained and Non-maintained operation, 3 hour duration
- EasiCheck addressable testing. System detailed on page 304
- Central system slave versions
- Semi-recessing flanged bezel attachment

### Specification

Self contained - To specify state: BSI Kitemarked and ICEL registered, IP65 self contained emergency luminaire, with ABS base, clip-in geartray and polycarbonate clip-on diffuser, as JSB Zeta II range, part no. \_\_\_\_\_

Slave - To specify state: Central system compatible slave, IP65 emergency luminaire, with ABS base, clip-in geartray and polycarbonate clip-on diffuser, as JSB Zeta II range, part no. \_\_\_\_\_

### Dimensions



Options	L (mm)	W (mm)	D/D1 (mm)	D2 (mm)	Cut out (mm)
Surface mounted	351	95	75	-	-
Semi-recessed	390	132	31	44	345 x 85

### Photometric Data

Luminaire type	Mounting height (m)	Escape route 2m wide 1 lux min					Open (anti-panic) area 0.5 lux min			
<b>Self-contained</b>										
NM	2.5	1.7	5.4	4.9	1.6	1.8	7.2	5.6	0.9	
	3.0	1.6	5.2	4.8	1.3	1.8	7.2	6.0	0.9	
	4.0	-	-	-	-	1.6	7.5	6.5	1.4	
M	2.5	1.5	5.0	4.6	1.4	1.7	7.0	5.4	1.5	
	3.0	1.3	4.8	4.4	1.0	1.6	7.0	5.7	1.5	
	4.0	-	-	-	-	1.4	7.0	6.2	1.1	
<b>Slave</b>										
AC/DC	2.5	2.5	7.2	6.0	2.3	2.6	7.4	5.3	2.1	
	4.0	1.0	7.0	6.7	1.9	2.5	7.5	6.3	2.3	
	6.0	-	-	-	-	1.8	7.0	6.6	1.8	
AC/AC	2.5	3.0	8.4	6.0	2.6	2.9	10.9	7.0	1.5	
	4.0	2.9	8.4	7.6	2.6	2.9	11.8	8.7	1.9	
	6.0	0.5	8.2	7.4	0.5	2.9	11.8	10.5	1.9	

### Catalogue Numbers

System Mode	Cat No	Weight (kg)
Non Maintained 3Hr	ZE83ICEL	1.2
Non Maintained 3 Hr EasiCheck	ZE83ICELEC	1.3
Non Maintained 3 Hr EasiCheck 2	ZE83ICELEC2	1.3
Maintained 3Hr	ZE83MICEL	1.3
Maintained 3Hr EasiCheck	ZE83MICELEC	1.4
Maintained 3Hr EasiCheck 2	ZE83MICELEC2	1.4
230V Ceaguard Slave	ZE8230CG	0.9
230V AC Mains Slave	ZE88230	0.9
50V AC/DC Central System Slave	ZE850	0.9
110V AC/DC Central System Slave	ZE8110	0.9

Accessories	Cat No	Weight (kg)
Semi-recess mounting bezel	ZE8FM	0.1
European Format self-adhesive legend kit	ZELK	0.05